

## **PRODUCT DATASHEET**

# Enhanced anti-glare,Led spot light HYD-343S-7W\*3 4000K



# **Application**

- Home
- Restaurant
- Exhibition Hall
- Stage
- Conference Room
- Clothing Store

# **Benefits**

- · Flicker free
- It can be used for emphasis lighting and decorative lighting
- Spot light have prominent advantages in commercial lighting
- No secondary light spot, it can create a wall washing effect

#### **Features**

- Warranty 5 years
- PC,Good light transmission
- Small size, light weight, buckle design, easy to install
- Die-cast aluminum, good heat dissipation, reduce light decay





#### **Electrical Data**

Nominal wattage (W)	7W*3	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50	
Nominal Current (mA)	183	
LED Driver Current (mA)	300	
LED Driver Voltage (VDC)	15-24	
LED Driver Efficiency (%)	80%	
Power Factor λ	0.5C	
Total harmonic distortion (%)		
Operating mode	External LED driver	

#### **Photometrical data**

Luminous flux ±10% (lm)	2408 lm	
Luminous efficacy	108 lm/w	
Color temperature	4000K	
Light color (designation)	Natural White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	5585	
Flickering	Flicker free	
Beam angle	32 °	






4000K



**Dimensions & Weight** 

Diameter (mm)	250*85
Height (mm)	40
Product weight (g) / Housing	490



#### **Material & Colors**

Product color	White	
Housing color	White	
Body material	Aluminum	
Cover material	PC	
Mercury content	0.0 mg	

# **Application & Mounting**

Ambient temperature range	-20°C~+45 °C		
Temperature range at storage	-20°C~+60 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recessed		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	235*73		
LED module replaceable	Not replaceable		
With light source	Yes		




## **Certificates & Lifespan**

Life (h)	50,000	
Certificates	CB CE LVD EMC	
Standards	ISO9001:2015	

## **Logistical Data**

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-343S-7W*3	•••			•••

## **Installation Method**



#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.