

## PRODUCT DATASHEET

### Track Light HYD-610-30W 3000K



---

### Application

- Hotel
- Mall
- Supermarket
- Theater
- Shop

---

### Benefits

- Flicker free
- Adjustable Angle, flexible light control
- Minimum Glare, more clear and comfortable
- High color rendering index, restore the true color of the object, show its beauty

---

### Features



- Warranty 2 years
- High efficiency lens design, resulting in a clear edge of the soft spot
- Good heat dissipation performance, protect the chip, extend the service life

## Electrical Data

Nominal wattage (W)	<b>30W</b>
Nominal Voltage (V)	220-240 V
Mains Frequency (Hz)	50
Nominal Current (mA)	121
LED Driver Current (mA)	135mA±5%
LED Driver Voltage (Vdc)	186 Vdc
LED Driver Efficiency (%)	93%
Power Factor λ	0.9
Total harmonic distortion (%)	...
Operating mode	External LED driver

## Photometrical data


Luminous flux ±10% (lm)	1929 lm
Luminous efficacy	71 lm/w
Color temperature	<b>3000K</b>
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	≤5 SDCM
Luminous intensity/cd	8665
Flickering	Flicker free
Beam angle	25 °



**3000K**

## Dimensions & Weight

Diameter (mm)	75
Height (mm)	168
Product weight (g)	...



## Material & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	PC
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-10°C~+40 °C
Temperature range at storage	-10°C~+40 °C
Type of connection	Screwless terminal
Type of protection	IP20
Dimmable	No
Mounting type	Track mounted
Mounting location	Ceiling
Application environment	Indoor
Cut size (mm)	No
LED module replaceable	Not replaceable
With light source	Yes


## Certificates & Lifespan

Life (h)	20,000
Certificates	CB LVD EMC RoHS
Standards	ISO9001:2015

## Logistical Data

Product code	Dimensions (L*W*H)	Pcs/ carton	G.W. kg	Volume CBM
HYD-610-30W	41*30.5*47.5 cm	30	...	0.05940

## Installation Method



## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release